

Amendments to the Claims:

This listing of claims will replace all prior versions, and listing of claims in the application.

Listing of Claims:

1. (previously presented) A motor vehicle designed to carry a fold-up warning triangle which can be removed from the vehicle, the vehicle comprising:

an opening having a boundary edge;

a hatch for covering said opening, said hatch being arranged so that it can move between a closed position and an open position; and

an edge portion of said hatch able to secure said fold-up warning triangle in a folded-up position, said edge portion bearing against the boundary edge of the opening in the closed position of said hatch.

wherein a reflector material carried by said fold-up warning triangle is visible to other traffic when said hatch is in its open position.

2. (previously presented) The motor vehicle according to claim 1 wherein said reflector material carried by said fold-up warning triangle is situated on one of three legs of said fold-up warning triangle.

3. (previously presented) The motor vehicle according to claim 1, further comprising a recess in said edge portion of said hatch, said fold-up warning triangle being releasably fitted therein, said recess having a wall interrupted by at least one hole through which said reflector material carried by said fold-up triangle is visible to other traffic when said hatch is in its open position.

4. (original) The motor vehicle according to claim 3 wherein said hole is triangle-shaped as a symbolic representation of the shape of said warning triangle in its deployed position.

5. (original) The motor vehicle according to claim 3 wherein said wall of said recess is interrupted by a number of holes arranged alongside each other.

6. (original) The motor vehicle according to claim 3 wherein said wall plane of said recess is interrupted by three holes arranged alongside each other.

7. (original) The motor vehicle according to claim 1 wherein said a warning surface is oriented essentially at right angles to a road surface used by the vehicle when said hatch is in the opened position.

8. (original) The motor vehicle according to claim 1 wherein two warning triangles are releasably fitted in respective recesses in said edge portion of said hatch.

9. (New) A motor vehicle designed to carry a fold-up warning triangle which can be removed from the vehicle, the vehicle comprising:

an opening having a boundary edge;

a hatch for covering said opening, said hatch being arranged so that it can move between a closed position and an open position; and

an edge portion of said hatch able to secure said fold-up warning triangle in a folded-up position, said edge portion bearing against the boundary edge of the opening in the closed position of said hatch,

wherein a reflector material carried by said fold-up warning triangle is visible to other traffic when said hatch is in its open position, wherein said reflector material carried by said fold-up warning triangle is situated on one of three legs of said fold-up warning triangle.